



## F616 1.25U-4Slot Chassis

**Part Number:** F616-CH04



### Overview

F616 is a new generation high-capacity transmission platform for fiber optical networks. It is suitable for country, province, state, city backbone and metro networks to meet T-Bit capacity requirements. It offers flexible and cost-effective solutions for IDC, ISP operators to build large granular WDM transmission networks. CH04 is a compact 1.25U rack size chassis with 4 business slot on the front panel and 1 management slot on the back panel.

### Applications

- Country, Province, State, City backbone and metro network
- Metro DWDM distance extension
- Long-Haul transmission system

### Features

- 1.25U 19" Rack Compact size
- 4 Slots for Business module cards
- Modular design for Power and FAN module
- Hot Pluggable, Easy Replacement
- 1+1 Balanced and Redundancy Power supply,
- AC / DC optional
- Support SNMP-based Network management
- Support CLI, WEB, Telnet and NMS
- Visual Graphic information interface
- Support Entire network topology, elements auto-discovery and generation
- Support Voice alarm, e-mail alerts, SMS alerts, Real-time online remote monitoring



## Specification

Parameter		Technical indicators
Size (mm)		1.25U 19" : 482.6(W) x 360(D) x 55(H)
Slot		4 Slots for Business module cards
Power Supply		Dual Power Supply 100~240VAC, -48VDC optional
FAN		3*FAN
Environment	Operating Temperature	-10 ~ 60 °C
	Storage Temperature	-40 ~ 85 °C
	Relative Humidity	5 ~ 95 RH%

## Ordering Information

Part No.	Description
CH04DD	1.25U-4Slot Chassis with 2* -48VDC
CH04AD	1.25U-4Slot Chassis with 1* 100~240VAC + 1* -48VDC
CH04AA	1.25U-4Slot Chassis with 2* 100~240VAC