FICER Technology Co., Ltd.
明虹科技股份有限公司

2F, No.138, Daye Rd., Beitou Dist.,
Taipei City 112030, Taiwan
www.Ficer.com

SKU: 0TF0N47-xx

25G SFP28 CWDM Transceiver
Hot Pluggable, Duplex LC, CWDM DFB, SMF 10km, DDM, C-Temp

Part Number: FSPP-N7-Cxx-10DQ



Overview

FSPP-N7-Cxx-10DQ is a Small Form Factor Pluggable SFP28 transceiver compliant with SFF-8402 SFP28 MSA standard. The high performance uncooled CWDM DFB transmitter and high sensitivity PIN receiver with built-in CDR provide superior performance for 25GBASE-LR Ethernet, CPRI Option #10 and 25G CWDM Networks applications up to SMF 10km optical links.

Applications

- 25GBASE-LR Ethernet @25.78125G
- CPRI Option #10 @24.33G
- eCPRI 5G Mobile Networks
- 25G CWDM Networks

Features

- Compatible with IEEE802.3cc 25GBASE-LR
- Compliant with CPRI option10
- Compliant with SFF-8402 SFP28 MSA
- Compliant with SFF-8431, SFF-8432 SFP+ MSA
- Data Rate up to 25.78125Gbps
- Built-in CDR on both Transmitter and Receiver
- Hot Pluggable
- Uncooled CWDM DFB laser transmitter and PIN receiver
- 6 CWDM Wavelength 1271~1371nm available
- Duplex LC connector
- 2-wire interface for management and diagnostic monitor compliant with SFF-8472
- Single +3.3V power supply
- Link distance 10km over SM fiber
- Operating Temperature 0~+70°C
- Maximum Power consumption 1.5W
- Metal SFP enclosure with low EMI and connector latch
- CE, FCC Compliant
- RoHS Compliant

TEL+886-2-2898-3830 FAX+886-2-2898-3840 Sales@Ficer.com

SKU: 0TF0N47-xx

Laser Safety

- This is a Class 1 Laser Product complies with 21 CFR 1040.10 and 1040.11 except for conformance with IEC 60825-1 Ed. 3., as described in Laser Notice No. 56, dated May 8, 2019.
- Caution: Use of control or adjustments or performance of procedure other than those specified herein may result in hazardous radiation exposure.

Absolute Maximum Ratings

Parameters	Symbol	Min.	Max.	Unit
Storage Temperature	T_{ST}	-40	+85	°C
Relative Humidity	RH	5	85	%
Supply Voltage	V_{CC}	-0.5	+3.6	V

Recommended Operating Conditions

Parameters	Symbol	Min.	Typ.	Max.	Unit
Case Operating Temperature	T_{OP}	0	-	+70	°C
Supply Voltage	V_{CC}	+3.13	+3.3	+3.47	V
Supply Current	I_{CC}	-	-	350	mA
Power Consumption	P			1.5	W

TEL+886-2-2898-3830 FAX+886-2-2898-3840 Sales@Ficer.com

SKU: 0TF0N47-xx

Transmitter Electro-optical Characteristics

V_{CC} = 3.13V to 3.47V, T_{OP} = 0 °C to +70 °C

Parameters		Symbol	Min.	Typ.	Max.	Unit	Note
Operating Line Rate			24.33	25.78125		Gb/s	
Optical Launch Power		Po	-7		+2	dBm	1
Optical Center Wavelength		λc	λc-6.5	λc	λc+6.5	nm	
Spectral Width (-20dB)		Δλ			1	nm	
Side Mode Suppression Ratio		SMSR	30			dB	
Optical Extinction Ratio		ER	3.5			dB	
Transmitter Dispersion Penalty	1271~1311nm	TDP			1	dB	2
	1331~1371nm				2		
Optical Eye Mask			IEEE 802.3cc				
Laser Off Power		P_{OFF}			-30	dBm	
Relative Intensity Noise		RIN			-130	dB/Hz	
Differential Data Input Swing		V_{IN}	180		850	mV	
Tx Disable Input Voltage-Low (Tx ON)		$TDISV_L$	GND		0.8	V	
Tx Disable Input Voltage-High (Tx OFF)		$TDISV_H$	2.0		V_{CC}	V	
Tx Fault Output Voltage-Low (Tx Normal)		$TFLTV_L$	GND		0.8	V	
Tx Fault Output Voltage-High (Tx Fault)		$TFLTV_H$	2.0		V_{CC}	V	

Note1: The optical power is launched into a 9/125μm single mode fiber.
Note2: After 10km G.652D 9/125μm single mode fiber.

Receiver Electro-optical Characteristics

V_{CC} = 3.13V to 3.47V, T_{OP} = 0 °C to +70 °C


Parameters	Symbol	Min.	Typ.	Max.	Unit	Note
Operating Line Rate		24.33	25.78125		Gb/s	
Receiver Sensitivity	SEN			-14.4	dBm	1
Maximum Receive Power	P_{RX-MAX}	+2			dBm	1
Optical Center Wavelength	λc	1260		1600	nm	
LOS De-Assert	LOS_D			-15	dBm	
LOS Assert	LOS_A	-30			dBm	
LOS Hysteresis	LOS_{HY}	0.5			dB	
Differential Data Output Swing	V_{OUT}	300		900	mV	
Receiver LOS Signal Output Voltage-Low	$LOSV_L$	GND		0.8	V	
Receiver LOS Signal Output Voltage-High	$LOSV_H$	2.0		V_{CC}	V	

Note1: Measured with a PRBS 2^{31}-1 test pattern @25.78125Gbps BER<$5x10^{-5}$.

TEL+886-2-2898-3830 FAX+886-2-2898-3840 Sales@Ficer.com

SKU: 0TF0N47-xx

Pin Assignment



Host PCB SFP28 Pad Assignment Top View

Pin Description

Pin	Name	Function / Description
1	VEET	Transmitter Ground
2	Tx_FAULT	Transmitter Fault Indication (1)
3	Tx_DISABLE	Transmitter Disable – Turns off transmitter laser output (2)
4	SDA	2-wire Serial Interface Data Line (SDA: Serial Data Signal) (3)
5	SCL	2-wire Serial Interface Clock (SCL: Serial Clock Signal) (3)
6	MOD_ABS	Module Absent, connected to VEET or VEER in the module (3)
7	RS0	Rate Select 0, optional (5)
8	Rx_LOS	Receiver Loss of Signal Indication (4)
9	RS1	Rate Select 1, optional (5)
10	VEER	Receiver Ground
11	VEER	Receiver Ground
12	RD-	Receiver Inverted Data output, AC coupled
13	RD+	Receiver Non-Inverted Data output, AC coupled

14	VEER	Receiver Ground
15	VCCR	Receiver 3.3V Power Supply
16	VCCT	Transmitter 3.3V Power Supply
17	VEET	Transmitter Ground
18	TD+	Transmitter Non-Inverted Data Input, AC coupled
19	TD-	Transmitter Inverted Data Input, AC coupled
20	VEET	Transmitter Ground

Note1: Tx Fault is open collector/drain output which should be pulled up externally with a 4.7K~10KΩ resistor on the host board to supply <VccT+0.3V or VccR+0.3V. When high, this output indicates a laser fault of some kind. Low indicates normal operation. In the low state, the output will be pulled to <0.8V.

Note2: Tx Disable input is used to shut down the laser output per the state table below. It is pulled up within the module with a 4.7K~10KΩ resistor. 1) Low(0~0.8V): Transmitter on; 2) Between(0.8V and 2V): Undefined; 3) High (2.0~ VccT): Transmitter Disabled; 4) Open: Transmitter Disabled.

Note3: These are the module definition pins. They should be pulled up with a 4.7K~10KΩ resistor on the host board to supply less than VccT+0.3V or VccR+0.3V. MOD_ABS is grounded by the module to indicate that the module is present.

Note4: Rx_LOS (Loss of signal) is an open collector/drain output which should be pulled up externally with a 4.7K~10KΩ resistor on the host board to supply <VccT+0.3V or VccR+0.3V. When high, this output indicates the received optical power is below the worst case receiver sensitivity (as defined by the standard in use). Low indicates normal operation. In the low state, the output will be pulled to <0.8V.

Note5: Tied to ground through a 30K ohm resistor.

Digital Diagnostic Functions

As defined by the SFP MSA (SFF-8472) Ficer's SFP+ transceivers provide digital diagnostic functions via a 2-wire serial interface, which allows real-time access to the following operating parameters:


- Transceiver temperature
- Laser bias current
- Transmitted optical power
- Received optical power
- Transceiver supply voltage

It also provides a sophisticated system of alarm and warning flags, which may be used to alert end-users when particular operating parameters are outside of a factory-set normal range.

The operating and diagnostics information is monitored and reported by a Digital Diagnostics Controller (DDC) inside the transceiver, which is accessed through the 2-wire serial interface. When the serial protocol is activated, the serial clock signal (SCL pin) is generated by the host. The positive edge clocks data into the SFP+ transceiver into those segments of its memory map that are not write-protected. The negative edge clocks data from the SFP+ transceiver. The serial data signal (SDA pin) is bi-directional for serial data transfer. The host uses SDA in conjunction with SCL to mark the start and end of serial protocol activation. The memories are organized as a series of 8-bit data words that can be addressed individually or sequentially.

For more detailed information including memory map definitions, please see the SFP MSA (SFF-8472) Specification.

Digital Diagnostic Memory Map




Digital Diagnostic Monitoring Characteristics

Parameter	Accuracy	Unit	Note
Temperature	±3	°C	Internal Calibration
Supply Voltage	±0.1	V	Internal Calibration
Tx Bias Current	±5	mA	Internal Calibration
Tx Output Power	±3	dB	Internal Calibration
Rx Received Optical Power	±3	dB	Internal Calibration

SKU: 0TF0N47-xx

Mechanical Dimensions



(All Dimensions are ±0.20mm Unless Otherwise Specified, Unit: mm)

SKU: 0TF0N47-xx

Ordering Information

Part No.	Tx (xx=) & Latch Color	Link	DDM	Temp.
FSPP-N7-Cxx-10DQ	27=1271nm, Light Purple 29=1291nm, Sky Blue 31=1311nm, Yellow Green 33=1331nm, Yellow Ocher 35=1351nm, Pink 37=1371nm, Light Brown	SMF 10km	Yes	0~+70°C

Note: Distances are indicative only. To calculate a more precise link budget based on specific conditions in your application, please refer to the optical characteristics.

TEL+886-2-2898-3830 FAX+886-2-2898-3840 Sales@Ficer.com